

KYTOLA® Model TLA variable area flow meter is a sturdy industrial flow meter with heavy-duty impact resistant polymer flow tube.

This meter is a reliable instrument for measuring and monitoring large lubrication oil flows.



- For oil
- Sturdy construction
- Easy to read also with dark oils
- Alarm-ready

OIL FLOW METER TLA

FEATURES

Protected flow tube

Relative scale 10–100% or direct reading scale in required flow unit

TYPICAL APPLICATIONS

Oil circulation lubrication monitoring in pulp & paper and steel mills

OPTIONS

Inductive low and/or high flow alarm

PES flow tube

Model	TLA
Flow range	Oil at 150 cSt: smallest range 0.5 – 32 L/min, max. range 12 – 170 L/min Oil at 220 cSt: smallest range 0.2 – 27 L/min, max. range 10 – 130 L/min
Connections	G 2" or NPT 2"
Max. pressure	20 bar
Max. temperature	80°C (*120°C)
Weight	3.3 kg
End blocks	Aluminium
Flow tube	Grilamid (PA-12), *PES
Float	AISI 329
Seals	Viton®

*) Special construction

TL	-			
End Block Material				
Aluminium (standard)	A			
Scale Maximum Oil Flow, 150 cSt oil, L/min (approx.)				
32				32
45				45
58				58
73				73
91				91
115				115
134				134
169				169
Scale				
10...100%			blank	
Factory assigned number for direct reading scale			xxxx	
Options				
Alarm readiness (standard)			D	
NPT connections			N	
PES flow tube			V	

Standard feature: leave *blank*

Special feature: choose character

